

RT-50
Standard Machine
Specifications

Operating Specifications:

- Operating Weight 5180 lbs | 2349 kg
- Ground pressure at operating weight maximum of 3.0 psi | 20.7kPa
- Rated operating capacity at 35% of tipping load 1400 lbs | 635 kg
- Operating capacity at 50% of tipping load 2000 lbs | 907 kg
- Tipping Loading of machine 4000 lbs | 1814 kg
- Ground clearance minimum of 14.4 inches | 366 mm
- Maximum machine width to outside of tracks 58.5 inches | 1486 mm

Aux. Hydraulic System:

- The standard auxiliary flow output should be a variable from 0 – 13.3 gpm (0-50 lpm)
- Standard flow system pressure to be 3000 psi | 20,684 kPa.

Operator Station:

- Heated cab enclosure
- Suspension seat
- 8-pin electronic attachment control

Service Refill Capacities:

- Fuel tank to hold 13 gal | 49 L
- Hydraulic tank to hold 3.5 gal | 13.2 L

Optional Attachments

- 60-inch Dirt Bucket with bolt on edge
- 42-inch pallet fork
- 60-inch Brush mower
- Dirt Auger
- 8"-12"-18"-24"-36" Auger Bits
- Broom Attachment
- Grader Bar
- Harley Rake (Soil Conditioner)
- Jackhammer
- Rock Bucket
- Stump Grinder
- Tiller Attachment
- Trencher