

# RT-65 MAX-Series Standard Machine Specifications

## Operating Specifications:

- Operating Weight 7480 lbs | 3393 kg
- Ground pressure at operating weight maximum of 4.2 psi | 29.0 kPa
- Rated operating capacity at 35% of tipping load 1925 lbs | 873 kg
- Operating capacity at 50% of tipping load 2750 lbs | 1247 kg
- Tipping Loading of machine 5500 lbs | 2495 kg
- Ground clearance minimum of 12.9 inches | 328 mm
- Maximum machine width to outside of tracks 66 inches | 1676 mm

## Aux. Hydraulic System:

- The standard auxiliary flow output should be a variable from 0 – 22.2 gpm (84 lpm)
- Standard flow system pressure to be 3300 psi | 22,750 kPa

## Service Refill Capacities:

- Fuel tank to hold 23.2 gal | 87.8 L
- Hydraulic tank to hold 3.3 gal | 12.5 L

## Machine Options

- All weather cab with heat and A/C (indented included as standard with all MAX-Series cabs)
- Bluetooth Radio with USB
- Mechanical Suspension seat
- 8-pin electronic attachment control
- 2-speed travel (10.6 mph / 17.1 Kph)
- Hydraulic Quick Attach
- Back-up camera

## Optional Attachments

- 67-inch Dirt Bucket w/ bolt on cutting edge
- Pallet Fork, 48-inch
- 60-inch Brush mower
- 72" Brush Grapple
- Dirt Auger
- 8"-12"-18"-24"-36" Auger Bits
- Broom Attachment
- Grader Bar
- Harley Rake (Soil Conditioner)
- Jackhammer
- Rock Bucket

- Stump Grinder
- Tiller Attachment
- Landscape Seeder
- Trencher
- Truss Jib
- Snow Bucket