

RT-75 Heavy Duty MAX-Series Standard Machine Specifications

Operating Specifications:

- Operating Weight shall be 9210 lbs | 4178 kg
- Ground pressure at operating weight maximum of 3.6 psi | 24.8 kPa
- Rated operating capacity at 35% of tipping load shall be 2800 lbs | 1270 kg
- Operating capacity at 50% of tipping load shall be 4000 lbs | 1814 kg
- Tipping Loading of machine shall be 8000 lbs | 3629 kg
- Ground clearance shall be minimum of 14.4 inches | 366 mm
- Maximum machine width to outside of tracks shall be 70 inches | 1778 mm

Aux. Hydraulic System:

- The low flow auxiliary output should be a variable from 0 – 22.6 gpm (85.5 lpm)
- The Pump capacity for the high flow shall be 35.7 gpm (135 lpm)
- High flow shall be selectable to operate via thumb operated rocker switch from 0-35.7 GPM
- Standard flow system pressure be 3300 psi | 22,750 kPa
- High flow system pressure to be 3300 psi | 22,750 kPa

Operator Station:

- All weather cab with heat and A/C
- Bluetooth Radio with USB
- Suspension air ride seat
- Back-up camera
- Self-leveling bucket
- Hydraulic quick attach
- Ride Control

Service Refill Capacities:

- Fuel tank to hold 18.4 gal | 70 L
- Hydraulic tank to hold 8 gal | 30 L

Optional Attachments

- 72-inch Dirt Bucket w/ bolt on cutting edge
- Pallet Fork, 48-inch
- Brush Grapple, Tine 72 Inch
- 72" High Flow Brush Cutter
- Dirt Auger
- 8"-12"-18"-24"-36" Auger Bits
- Broom Attachment
- Grader Bar

- Harley Rake (Soil Conditioner)
- Jackhammer
- Rock Bucket
- Stump Grinder
- Tiller Attachment
- Landscape Seeder
- Trencher
- Tree Spade
- Snow Bucket
- Snow Blower
- Truss Jib